



SR-5020 Subframe Hoist Class 50 / E



The new Rugby SR-5020 truck hoist is tested at full-rated capacity for an extended life cycle when all recommended maintenance is adhered to. The Class 50 SR-5020 hoist can be ordered in lieu of the HR-550 in certain applications, and is ideally suited to the Medium Duty market.

- Class 50 Dump / Class E Conversion
- Approximate weight: 710 lbs*
- 10' subframe
- Available with double acting electric pump or direct mount gear pump
- Cylinder specifications: 6" bore; 20" stroke; 2-1/2" diameter rod
- Mounting height: 11.3 inches
- Capacity range: 9.1 - 17 tons
- Factory tested for durability & performance
- Integrated body prop
- Mounting distance: 90.25"

* Approximate weight includes hoist, subframe, mounting accessories and power unit

All specifications are subject to change without notice.

Body Length	CA	Rear Overhang	Capacity @ 50° Dump Angle (tons)
10'	84"	6"	12.9
11'	84"	18"	13.2
11'	84"	6"	10.8
12'	84"	30"	17.0
12'	84"	18"	13.2
12'	108"	6"	10.8
14'	108"	30"	13.2
14'	108"	18"	10.8
14'	120"	18"	10.8
14'	120"	6"	9.1
16'	120"	42"	13.2
16'	120"	30"	10.8

Commitment to Quality

Today's marketplace demands quality products And competitive pricing. We work hard at Rugby to fulfill all your needs. Our reputation since 1969 has been one of quality production customer satisfaction.



RUGBY MANUFACTURING

Rugby, ND • 701-776-5722 • Fax 701-776-6235

www.rugbymfg.com • Email sales@rugbymfg.com

a TBEI company
TRUCK BODIES & EQUIPMENT INTERNATIONAL, INC.