



515 1st St. NE
Rugby, ND 58368-1209


800-869-9162
www.RUGBYMFG.com

Rugby® Hy-Flo™ Twin Electric Power Unit

Unit features include fast cycle time & simplified operation for multiple users


Rugby® Manufacturing is pleased to announce that we are now offering the Rugby Hy-Flo™ Twin Electric Power Unit. This unit is available for use with select Rugby hoists.

This system offers **3x** the capacity of the standard electric double-acting unit, and also offers up to **1.2x** the capacity of a PTO at idle.



Ordered in lieu of direct mount hydraulics, the Rugby Hy-Flo Twin Electric Power Unit offers features and benefits that meet and exceed current systems:

- Can save you up to **\$1,500**, and cut installation time by up to 2/3
- Save up to **\$500** off of the cost of your chassis when ordering – no PTO option required
- Push button control for simple operation
- No chance of leaving PTO engaged
- Can help your customer with Idle Restrictions
- No linkages



Specifications of this unit include:

- Number of Motors / Pumps	2
- Voltage	12 VDC
- Avg Current Draw per Motor (loaded body)	231 Amps
- Nominal Flow	6 GPM
- Average Flow (loaded body)	3.3 GPM
- Rated Pressure	3200 PSI
- Batteries Required	2

This unit can be used with the following hoists:

- LR26 • LR623
- LR28

For more information on the Rugby Hy-Flo Twin Electric Power Unit, please contact your Rugby Distributor today!